


*Temperature sensor
PT 100 with grip handle*
Special Fermenting room

CROS - R - 1700




- Class A Pt 100
- Measuring range from **-50°C to +250°C**
- Length of 1700 mm, others on request
- Stainless steel protection sheath
- Stainless steel grip handle
- Tip with shrink for a very fast response time
- Probes compatible with KISTOCK temperature dataloggers and portable thermometers

Special probes **Fermenting room** allow to measure temperature in the specific conditions of wine-making process.



■ Description

Grip handle



Reinforced cable output with flexible
Shielded Teflon cable

Shrink



Protection sheath in food-
industry stainless steel 316 L
Ø 10 mm, shrink in 6 mm

■ Specifications

Probe	Length	Range	Accuracy	Compatible with...
CROS-R-1700	1700 mm	from -50 to +250°C	±0.4% of reading* or ±0.3°C	Portable thermometers : TR100

*All accuracies indicated in this document were stated in laboratory conditions and can be guaranteed for measurements carried out in the same conditions, or carried out with required compensation. The accuracy is expressed either by a deviation in °C, or by a percentage of the value concerned. Only the bigger value is considered.


■ Optional

- Protection cover IP65.
- Calibration certificate.
- Portable thermometers .
- Temperature datalogger

With KISTOCK temperature datalogger



With portable thermometers



www.kimo.fr

Distributed by :

EXPORT DEPARTMENT

Tel : + 33. 1. 60. 06. 69. 25 - Fax : + 33. 1. 60. 06. 69. 29

e-mail : export@kimo.fr

